



MULTI-ROOM® / ARIA

ERGONOMIC



MORETTI
DESIGN
WI-FI

L'interfaccia che permette la gestione remota tramite SMARTPHONE di ultima generazione.

Interface that allows remote management by SMARTPHONE.

Gestion de l'appareil depuis un SMARTPHONE de dernière génération.

Interfaz que permite la gestión remota a través SMARTPHONE de última generación.

Modul, Schnittstelle, die Remote-Management via SMARTPHONE der letzten Generation ermöglicht.



TRITTICO
INOX

Griglie frontali realizzate in acciaio inox, segno di riconoscimento della MORETTI DESIGN.

Front grids made of stainless steel, recognition sign of MORETTI DESIGN.

Grilles avant en acier inoxydable, signe distinctif de MORETTIDESIGN.

Rejillas frontales de acero inoxidable, un signo de reconocimiento de MORETTI DESIGN.

Frontgitter aus Edelstahl, Erkennungszeichen von MORETTI DESIGN.



ASH
DRAWER

Cassetto per la raccolta delle ceneri.

The heat exchanger is automatically cleaned.

Cendrier.

Cajón cenicero.

Ausziehbare Aschelade.



MAGICAL
GLASS

Consente la visione della camera di combustione solo a fiamma accesa.

It allows the view of combustion chamber only when the flame is lit.

Il permet de visualiser la chambre de combustion uniquement lorsque la flamme est allumée.

Permite ver la cámara de combustión solo con la llama encendida.

Glas ermöglicht die Betrachtung der Brennkammer nur bei brennender Flamme.

TECHNOLOGY



OPTIONAL



ERGONOMIC — MULTI-ROOM® / ARIA

	Potenza Globale Global Power Puissance globale Potencia global Verbrennungsleistung	Potenza Nominale Nominal Power Puissance Nominale Potencia Nominal Nennleistung	Rendimento totale Total efficiency Rendement globale Potencia global Pellet Wirkungsgrad	Peso Weight Poids Peso Gewicht	Consumo min-MAX Min-Max consumption Consumation min-MAX Consumo min-max Min-Maxi verbrauch	Temperatura gas di scarico Exhaust gas temperature Température des gaz d'échappement Temperatura de los gases de escape Abgasstemperatur	Tiraggio richiesto in funzionamento Draw required in operation Dessiner nécessaire en fonctionnement Dibujar requerido en la operación Erforderlicher Betriebszug	Uscita fumi Chimney Output Sortie conduit de cheminée Salida conducto de humos Rauchauslass	Ingresso aria Air intel Entrée d'air Entrada aire Lufteinlass	Serbatoio pellet Pellet tank Réservoir Deposito Tank, Fassungsvermögen	Assorbimento elettrico watt Electric consumption watt Absorption électrique watt Consumo de electricidad watt Elektrischer Verbrauch watt
	KW	KW	%	KG	KG/H	°C	PA	MM	MM	KG	W
14 kw	14,0	12,7-3,0	90,6	155	0,65-2,92	182	3	80	60	17	M270-N93-R45
12 kw	12,6	11,0-3,1	88,0	155	0,7-2,6	217	3	80	60	17	M270-N91-R45
10 kw	10,1	9,0-3,1	88,0	155	0,7-2,0	189	3	80	60	17	M270-N89-R45

